



GENERAL NOTES TO CONTRACTOR

- 1.) Door frame profiles are manufactured according to SABS specification No. 1129 of 1977
- 2.) Always check the frames when building for squareness and plumb as they cannot be corrected afterwards
- 3.) After building in the contractor is to take all necessary measures to protect the frames from any on-site damage.

Motorized Roller Shutter Door		Type: 4500 x 5000mm	Quantity: 02	Type Mark: RS01
Door Description: XPanda Motorized Roller Shutter door with 5 Fenestra / vision laths at eye level with Polycarbonate inserts. Door is to comprise of 0.8 interlocking slats with nylon endlocks and aluminium T-bar. 75mm wide siderails on doors sized, 4500mm wide by 5000mm high and larger to prevent wind damage.		Frame Description: Galvanised Steel Frame as per approved manufacturer Finish: Description: Galvanised as per approved manufacturer in accordance with SABS 1461 Specifications		
Ironmongery: Refer to Ironmongery Schedule		Glazing: Clear Polycarbonate Inserts		
QUANTITIES TO BE VERIFIED PRIOR TO PLACEMENT OF ORDER. MASONRY OPENINGS TO BE VERIFIED ON SITE PRIOR TO COMMENCEMENT OF MANUFACTURE. SUPPLIER TO BE IN ACCORDANCE WITH ALL SABS AND NBR STANDARDS				



1st Floor, Office 4A,
Leadwood House, Cedar Square,
Bonza Bay Road, Beacon Bay,
East London 5241
TEL 043 726 7786
rob@intsika.com

MANUFACTURING FACILITY -IW4 IN ZONE 1A		DRAWN BY: A.T	CHECKED BY: C.G
ERF NO: 60948 & 60950		SCALE: 1: 50	
ISSUED FOR TENDER		DATE: 2021/06/03	PRINTING DATE: 2021/06/03
DRAWING NAME RS DOOR 01		DRAWING NO: CO 05-1.14	REVISION