



GENERAL NOTES TO CONTRACTOR

- 1.) Door frame profiles are manufactured according to SABS specification No. 1129 of 1977
- 2.) Always check the frames when building for squareness and plumb as they cannot be corrected afterwards
- 3.) After building in the contractor is to take all necessary measures to protect the frames from any on-site damage.

FFL
▽

Manual Sectional Door

Type:
2465 x 3000mm

Quantity:
01

Type Mark:
RS03B

Door

Description:

Manual Richards-Wilcox (Raynor) Sectional door with 38mm thick panel,
Model: RW T150 MR, fabricated from pre-painted white, hot dipped galvanised steel with rigid polyurethane insulation core for added strength and protection.

Tracks: 50.8mm Commercial galvanized track to be continuous angle mounted and fully adjustable to sealing door to jamb.

Counterbalance: Helically wound torsion springs mounted on continuous cross header shaft

Finish:

Description:

Bottom, Header and side weather seals contributing to a cleaner facility

Frame

Description:

Frame as per approved manufacturer

Mechanics:

Description:

Manual Operated

Finish:

Description:

Powder coated silver outside & white inside

Ironmongery:

Refer to Ironmongery Schedule

Glazing:

none

**QUANTITIES TO BE VERIFIED PRIOR TO PLACEMENT OF ORDER.
MASONRY OPENINGS TO BE VERIFIED ON SITE PRIOR TO COMMENCEMENT
OF MANUFACTURE.
SUPPLIER TO BE IN ACCORDANCE WITH ALL SABS AND NBR STANDARDS**



1st Floor, Office 4A,
Leadwood House, Cedar Square,
Bonza Bay Road, Beacon Bay,
East London 5241
TEL 043 726 7786
rob@intsika.com

MANUFACTURING FACILITY -IW4 IN ZONE 1A

DRAWN BY: A.T

CHECKED BY: C.G

ERF NO: 60948 & 60950

SCALE: 1: 50

ISSUED FOR **TENDER**

DATE: 2021/06/03

PRINTING DATE: 2021/06/03

**DRAWING NAME
RS DOOR 03B**

DRAWING NO:
CO 05-1.19

REVISION

