DOOR TYPE A — QUANTITY -

See Window Schedule Part 3 of 3
Drawing EL/DIA/C-8012

FFL

DOOR NUMBERS:	
DISCRIPTION:	
FRAME:	
IRONMONGERY:	
GENERAL:	

See Window Schedule Part 3 of 3
Drawing EL/DIA/C-8012

DOOR TYPE B — QUANTITY 1



FFL

DOOR NUMBERS:	**D07**
DISCRIPTION:	Level G3 bullet resistant anti-bandit door, overall size 900 x 2032mm. with 300 x 500mm high viewing panel glazed in 53mm thick clear glass supplied with 5-pin CISA dead lock with an additional heavy duty magnetic lock and striker including key switch and surface mounted casing, 6 Amp power supply, push buttons and interlock system, continuous roton type hinge, aluminium slam bar with heavy duty door closer (Dorma TS91) and D-style pull handles. Colour to later selection.
FRAME:	**Single rebated, 100 x 50 x 2mm gauge Galvanised mild steel door frame to suit left/right hand door, as indicated on ground floor plan. Galvinised surfaces to be cleaned down and washed to accept: 1 coat galvagrip primer, 1 coat universal undercoat and 2 coates plascon velvaglo enamel. All applied to manufacturer's specification. Colour to later selection.**
IRONMONGERY:	Ironmongery by manufacturer. Refer to ground floor plan, drawing EL/DIA/C-2000, for left/right hand door swing.
GENERAL:	**See door schedule for specifications and fire rating: SCH-8000.** **Access control by security personnel.** **To specialist specifications and details.**

DOOR TYPE C — QUANTITY 14



FFL

DOOR NUMBERS:	**D06, D11, D12, D14, D18, D23, D24, D28, D27, D38, D41, D44**
	Retain ALL Doors ; Remove Door 44
DISCRIPTION:	40mm thick single leaf, heavy duty interior solid core flush door with two concealed edges, size 900 x 2032mm high, 1 coat universal undercoat, 2 coats plascon velvaglo enamel. With 300x450mm aluminium ventilation grille, see drawing above and refer to General notes below. All to manufacturer's specification. Colour to later selection.
FRAME:	Durowin single rebated hot dip galvanised pressed steel door frame 1mm thick to suit left/right hand door, as indicated on ground floor plan, with base ties, 1 pair of steel butt hinges, rubber buffers and fixing lugs. Galvinised surfaces to be cleaned down and washed to accept: 1 coat galvagrip primer, 1 coat universal undercoat and 2 coates plascon velvaglo enamel. All applied to manufacturer's specification. Paint rear pressed steel lining with 2 coates of cold bitumastic solution, before building in frame. Colour to later selection.
IRONMONGERY:	**Ironmongery by specialist.** **Refer to ground floor plan, drawing EL/DIA/C-2000, for left/right hand door swing.**
GENERAL:	**See door schedule for specifications and fire rating: SCH-8000.**

DOOR TYPE D — QUANTITY 2



FFL

Retain D37;
Remove D35 Replace with window to fit opening of 900mm wide and 2100mm high.

DOOR NUMBERS:	D35, D37
DISCRIPTION:	40mm thick single leaf, heavy duty interior solid core flush door with two concealed edges, with 300 x 500mm high viewing panel glazed in 10mm thick clear glass, size 900 x 2032mm high, 1 coat universal undercoat, 2 coats plascon velvaglo enamel. All to manufacturer's specification. Colour to later selection.
FRAME:	Durowin single rebated hot dip galvanised pressed steel door frame 1mm thick to suit left/right hand door, as indicated on ground floor plan, with base ties, 1 pair of steel butt hinges, rubber buffers and fixing lugs. Galvinised surfaces to be cleaned down and washed to accept: 1 coat galvagrip primer, 1 coat universal undercoat and 2 coates plascon velvaglo enamel. All applied to manufacturer's specification. Paint rear pressed steel lining with 2 coates of cold bitumastic solution, before building in frame. Colour to later selection.
IRONMONGERY:	Ironmongery by specialist. Refer to ground floor plan, drawing EL/DIA/C-2000, for left/right hand door swing.
GENERAL:	See door schedule for specifications and fire rating: SCH-8000.

DOOR TYPE E — QUANTITY 2



FFL

Retain D17 and D25;
SAME AS NEW DOOR - ND08/P1 AT FIRST STOREY LEVEL

DOOR NUMBERS:	D17, D25
DISCRIPTION:	40mm thick single leaf, heavy duty interior solid core flush door with two concealed edges, with 300 x 500mm high viewing panel glazed in 10mm thick clear glass, size 1000 x 2032mm high, 1 coat universal undercoat, 2 coats plascon velvaglo enamel. With 300x450mm aluminium ventilation grille, see drawing above. All to manufacturer's specification. Colour to later selection.
FRAME:	Durowin single rebated hot dip galvanised pressed steel door frame 1mm thick to suit left/right hand door, as indicated on ground floor plan, with base ties, 1 pair of steel butt hinges, rubber buffers and fixing lugs. Galvinised surfaces to be cleaned down and washed to accept: 1 coat galvagrip primer, 1 coat universal undercoat and 2 coates plascon velvaglo enamel. All applied to manufacturer's specification. Paint rear pressed steel lining with 2 coates of cold bitumastic solution, before building in frame. Colour to later selection.
IRONMONGERY:	Ironmongery by specialist. Refer to ground floor plan, drawing EL/DIA/C-2000, for left/right hand door swing.
GENERAL:	See door schedule for specifications and fire rating: SCH-8000. Disabled Wc. door

DOOR TYPE F — QUANTITY 3

FFL

RETAIN AS FIRE EXIT DOORS - D16 ; D19 and D33

DOOR NUMBERS:	D16, D19, D33
DISCRIPTION:	Level G3 bullet resistant anti-bandit door, overall size 900 x 2032mm, supplied with 5-pin CISA dead lock with an additional heavy duty magnetic lock and striker including key switch and surface mounted casing connected to fire alarm system, 6 Amp power supply, continuous roton type hinge. Colour to later selection.
FRAME:	Single rebated, 100 x 50 x 2mm gauge Galvanised mild steel door frame to suit left/right hand door, as indicated on ground floor plan. Galvinised surfaces to be cleaned down and washed to accept: 1 coat galvagrip primer, 1 coat universal undercoat and 2 coates plascon velvaglo enamel. All applied to manufacturer's specification. Colour to later selection.
IRONMONGERY:	Ironmongery by specialist and manufacturer. Provide built-in magnetic lock connected to fire alarm system. Provide internal push bar for emergency exit. Refer to ground floor plan, drawing EL/DIA/C-2000, for left/right hand door swing.
GENERAL:	See door schedule for specifications and fire rating: SCH-8000 High security fire escape doors. Connected alarm system, to specialist detail and specification.

DOOR TYPE G — QUANTITY 1

FFL

RETAIN AS SERVER ROOM DOOR - D08

DOOR NUMBERS:	D08
DISCRIPTION:	Level G3 bullet resistant anti-bandit door, overall size 900 x 2032mm, supplied with 5-pin CISA dead lock with an additional heavy duty magnetic lock and striker including key switch and surface mounted casing, 6 Amp power supply, push buttons and interlock system, continuous roton type hinge, aluminium slam bar with heavy duty door closer (Dorma TS91) and D-style pull handles. Colour to later selection.
FRAME:	Single rebated, 100 x 50 x 2mm gauge Galvanised mild steel door frame to suit left/right hand door, as indicated on ground floor plan. Galvinised surfaces to be cleaned down and washed to accept: 1 coat galvagrip primer, 1 coat universal undercoat and 2 coates plascon velvaglo enamel. All applied to manufacturer's specification. Colour to later selection.
IRONMONGERY:	Ironmongery by specialist. Refer to ground floor plan, drawing EL/DIA/C-2000, for left/right hand door swing.
GENERAL:	See door schedule for specifications and fire rating: SCH-8000. Access control by security personnel. To specialist specifications and details.

DOOR TYPE H — QUANTITY 1

FFL

RETAIN AS DUCT DOOR - D32

DOOR NUMBERS:	D32
DISCRIPTION:	Single louvred door size 900x2032mm, comprising aluminium universal single bank extruded louvre blades fixed horizontally at 75mm pitch and angle of 45° fixed to total coverage mill finish aluminium frames clipped to 2mm aluminium mullions with bird guard and with visible door frame on steel support structure (in accordance with structural engineer's design) 1,6mm aluminium sheet sill and frames to be fixed with all necessary peripheral fixings.
FRAME:	Aluminium coupled unit comprising epoxy and polyester mix powder coated (50 - 100µ thick) aluminium side hung frame. Hung on three stainless steel washered aluminium butts.Frame to be sealed all round to full lengths of junction between plaster and frame with approved flexible sealant. Non-Standard powder coating colour: To be selected
IRONMONGERY:	Ironmongery by manufacturer. Refer to ground floor plan, drawing EL/DIA/C-2000, for left/right hand door swing.
GENERAL:	See door schedule for specifications and fire rating: SCH-8000.

DOOR TYPE J — QUANTITY 1

FFL

D40- REMOVE IF NOT REQUIRED/ LOCK UP - D40

DOOR NUMBERS:	D40
DISCRIPTION:	Vault door to be Gunnebo Security SANS 949:2005 approved, right hand opening, category 5 main door, constructed of 100mm barrier material, with double leaf swinging grille gate constructed of mild steel bar/tubing, overall mass 1982kg, with 1 x 4-wheel keyless combination lock with dial check lock and 2 x 8 lever keylocks on vault door and 2 x 5-lever high security keylocks on the grille gate with 4-way moving boltwork.
FRAME:	Frame by manufacturer.
IRONMONGERY:	Ironmongery by manufacturer.
GENERAL:	See door schedule for specifications and fire rating: SCH-8000.

INTERNAL DOORS

- Allow for supply and fit of solid timber internal doors and skirting boards where indicated. Painted to later selected colour.
- See door schedule for details of fire rating
- Door manufacturer to provide cross-cut sample of door for approval before doors are fabricated.
- All openings to be checked on site prior to fabrication.

Toughened glass

east london idz
business streamlined

No.	DATE	DESCRIPTION	APPR

CLIENT
EAST LONDON IDZ

PROJECT
REFURBISHMENT OF DIAMOND POLISHING FACTORY INTO OFFICES

DRAWING TITLE
EXISTING DOOR SCHEDULE PART 1/2

DRAWN	DESIGNED	CHECKED	DATE	SCALE	DRAWING No.	Rev.
HHUES	HHUES	RBAM	June,22	AS SHOWN	EL-IDZ- RDF11/21-18	0