


<div><div><div>NOTE: Dimensions shown are actual brickwork opening sizes. All dimensions to be checked and verified on site prior to manufacture.</div></div><div><div>900</div><div>2100</div></div></div>					<div><div><div>NOTE: Dimensions shown are actual brickwork opening sizes. All dimensions to be checked and verified on site prior to manufacture.</div></div><div><div>1574</div><div>2100</div></div></div>					<div><div><div>NOTE: Dimensions shown are actual brickwork opening sizes. All dimensions to be checked and verified on site prior to manufacture.</div></div><div><div>1200</div><div>2100</div></div></div>					<div><div><div>NOTE: Dimensions shown are actual brickwork opening sizes. All dimensions to be checked and verified on site prior to manufacture.</div></div><div><div>1200</div><div>2400</div></div></div>				
DOOR NO	POSITION	DOOR TYPE		QUANTITY	DOOR NO	POSITION	DOOR TYPE		QUANTITY	DOOR NO	POSITION	DOOR TYPE		QUANTITY	DOOR NO	POSITION	DOOR TYPE		QUANTITY
D01/P1	OFFICE	INTERNAL DOOR		1	D02/P1	OFFICE	INTERNAL DOOR		1	D03/P1	HOIST	INTERNAL DOOR		1	D04/P1	Balcony	EXTERNAL FIRE DOOR		2
DESCRIPTION  900 x 2100 mm High aluminium hinged pivot door with NO side light panes. Leaf hung on Dorma BTS 80 with 90 deg hold open option.  FRAME SECTION Wispeco Aluminium 38MM Section          GLAZING:  Side Panes 6.38 mm clear Laminated safety glazing to fixed and opening sections on side panes. Door 6.38mm Laminated Safety Glass  FINISH: Black powder coated 25 micron.  EXTRAS: nil					DESCRIPTION  900 x 2100 mm High aluminium hinged pivot door with 1 X 600mm Side light panel. Leaf hung on Dorma BTS 80 with 90 deg hold open option.  FRAME SECTION Wispeco Aluminium 38MM Section          GLAZING:  Side Panes 6.38 mm clear Laminated safety glazing to fixed and opening sections on side panes. Door 6.38mm Laminated Safety Glass  FINISH: Black powder coated 25 micron.  EXTRAS: nil					DESCRIPTION  1200 x 2100 mm High aluminium hinged Sliding door- automated to work with hoist operation. To be fitted in Existing Frame By Specialist.  FRAME SECTION Wispeco Aluminium 38MM Section          GLAZING:  Side Panes 6.38 mm clear Laminated safety glazing to fixed and opening sections on side panes. Door 6.38mm Laminated Safety Glass  FINISH: Black powder coated 25 micron.  EXTRAS: nil					SPECIFICATION:  Wispeco Aluminium <b>1200mm Single</b> Door with Glass .FIRE DOOR With; Frame powder coated (50 - 100µ thick) aluminium door (complying with AAAMSA performance criteria A2), size 900.00 x 2,400.00mm high x 44mm thick ; Glazing- Glazed with 6.38mm laminated safety glass in accordance with NBR part N, SABS 0137 Edition 3 2000, SABS 0400, SABS 1263 and AAAMSA selection guide for safety glazing materials fixed inside jambs of opening.  FRAME:  WISPECO aluminium frame/ equal and approved (No timber subframe: NK26 stiffening mullion by specialist if required), or equal approved.  GLAZING: 6.38 mm laminated safety glazing to fixed and opening sections.  FINISH: Black powder coated 25 micron.  EXTRAS: nil				

<div><div><div>NOTE: Dimensions shown are actual brickwork opening sizes. All dimensions to be checked and verified on site prior to manufacture.</div></div><div><div>820</div><div>874</div><div>874</div><div>2060</div><div>714</div></div></div>					<div><div><div>NOTE: Dimensions shown are actual brickwork opening sizes. All dimensions to be checked and verified on site prior to manufacture.</div></div><div><div>820</div><div>874</div><div>874</div><div>2060</div></div></div>					<div><div><div>NOTE: Dimensions shown are actual brickwork opening sizes. All dimensions to be checked and verified on site prior to manufacture.</div></div><div><div>974</div><div>920</div><div>2137</div></div></div>					<div><div><div>NOTE: Dimensions shown are actual brickwork opening sizes. All dimensions to be checked and verified on site prior to manufacture.</div></div><div><div>974</div><div>2137</div></div></div>				
DOOR NO	POSITION	DOOR TYPE		QUANTITY	DOOR NO	POSITION	DOOR TYPE		QUANTITY	DOOR NO	POSITION	DOOR TYPE		QUANTITY	DOOR NO	POSITION	DOOR TYPE		QUANTITY
D05/P1	Store	INTERNAL DOOR		1	D06/P1	Store	INTERNAL DOOR		1	D07/P1	ABLUTIONS	INTERNAL DOOR		1	D08/P1	Ablutions	INTERNAL PARAPLEGIC DOOR		1
POSITION: As per plan. Contractor to check floor plans for LH/RH openings. SPECIFICATION  DOOR TYPE Swartland semi - exteroir door. Bergsun Doors. Horizontal Commercial or equal and approved. Product Code : BSH RZMS2  DESCRIPTION Semi Exterior carved in Class : Medium Duty Size : 813 X 2032 2CE  DOOR FINISH: All blemishes in timber to be filled and sanded down and prepared for painting. 3 coats Mahogany stain tinted Rystix timber sealer, applied generously to ensure brush marks flow out to smooth, even coat. Colour: To approval.  IRONMONGLERY: HANDLES Handle Type Tubular stainless Steel TH124 Latch , KH or CYL ESCUTCHEONS DKE-001 Keyhole per pair DOOR STOP DDS-SS-017 HINGES DNW-W-010. 102 x75 x3mm Aluminium nylon washered butt hinge per pair. LOCKS D034S Multiple lever sash lock (SS) Each. (PB) Each.   GLASS: NO FANLIGHT.  FRAME: Swartland : SK1B 90 x 70mm rebated meranti door frame and fanlight ; 19mm quadrant  Frame fixed to wall with standard Hilti metal screws with nylon cover countersunk and plugged.  Frame to receive 19 mm meranti quadrant both sides  FRAME FINISH: Stained and sealed to match quadrant finish.					POSITION: As per plan. Contractor to check floor plans for LH/RH openings. SPECIFICATION  DOOR TYPE Swartland semi - exteroir door. Bergsun Doors. Horizontal Commercial or equal and approved. Product Code : BSH RZMS2  DESCRIPTION Semi Exterior carved in Class : Medium Duty Size : 813 X 2032 2CE  DOOR FINISH: All blemishes in timber to be filled and sanded down and prepared for painting.3 coats Mahogany stain tinted Rystix timber sealer, applied generously to ensure brush marks flow out to smooth, even coat. Colour: To approval.  IRONMONGLERY: HANDLES Handle Type Tubular stainless Steel TH124 Latch , KH or CYL ESCUTCHEONS DKE-001 Keyhole per pair DOOR STOP DDS-SS-017 HINGES DNW-W-010. 102 x75 x3mm Aluminium nylon washered butt hinge per pair. LOCKS D034S Multiple lever sash lock (SS) Each. (PB) Each.   GLASS: NO FANLIGHT.  FRAME: Swartland : SK1B 90 x 70mm rebated meranti door frame and fanlight ; 19mm quadrant  Frame fixed to wall with standard Hilti metal screws with nylon cover countersunk and plugged.  Frame to receive 19 mm meranti quadrant both sides  FRAME FINISH: Stained and sealed to match quadrant finish.					POSITION: As per plan. Contractor to check floor plans for LH/RH openings. SPECIFICATION  DOOR TYPE Swartland semi - exteroir door. Bergsun Doors. Horizontal Commercial or equal and approved. Product Code : BSH RZMS2  DESCRIPTION Semi Exterior carved in Class : Medium Duty Size : 813 X 2032 2CE  DOOR FINISH: All blemishes in timber to be filled and sanded down and prepared for painting.3 coats Mahogany stain tinted Rystix timber sealer, applied generously to ensure brush marks flow out to smooth, even coat. Colour: To approval.  IRONMONGLERY: HANDLES Handle Type Tubular stainless Steel TH124 Latch , KH or CYL ESCUTCHEONS DKE-001 Keyhole per pair DOOR STOP DDS-SS-017 HINGES DNW-W-010. 102 x75 x3mm Aluminium nylon washered butt hinge per pair. LOCKS D034S Multiple lever sash lock (SS) Each. (PB) Each.   GLASS: NO FANLIGHT.  FRAME: Swartland : SK1B 90 x 70mm rebated meranti door frame and fanlight ; 19mm quadrant  Frame fixed to wall with standard Hilti metal screws with nylon cover countersunk and plugged.  Frame to receive 19 mm meranti quadrant both sides  FRAME FINISH: Stained and sealed to match quadrant finish.					POSITION: As per plan. Contractor to check floor plans for LH/RH openings. SPECIFICATION  DOOR TYPE Swartland semi - exteroir door. Bergsun Doors. Horizontal Commercial or equal and approved. Product Code : BSH RZMS2  DESCRIPTION Semi Exterior carved in Class : Medium Duty Size : 813 X 2032 2CE  DOOR FINISH: All blemishes in timber to be filled and sanded down and prepared for painting.3 coats Mahogany stain tinted Rystix timber sealer, applied generously to ensure brush marks flow out to smooth, even coat. Colour: To approval.  IRONMONGLERY: HANDLES Handle Type Tubular stainless Steel TH124 Latch , KH or CYL ESCUTCHEONS DKE-001 Keyhole per pair DOOR STOP DDS-SS-017 HINGES DNW-W-010. 102 x75 x3mm Aluminium nylon washered butt hinge per pair. LOCKS D034S Multiple lever sash lock (SS) Each. (PB) Each.   GLASS: NO FANLIGHT.  FRAME: Swartland : SK1B 90 x 70mm rebated meranti door frame and fanlight ; 19mm quadrant  Frame fixed to wall with standard Hilti metal screws with nylon cover countersunk and plugged.  Frame to receive 19 mm meranti quadrant both sides  FRAME FINISH: Stained and sealed to match quadrant finish.				

	No.	DATE	DESCRIPTION	APPR	CLIENT EAST LONDON IDZ						
						PROJECT REFURBISHMENT OF DIAMOND POLISHING FACTORY INTO OFFICES					
						DRAWING TITLE NEW DOOR SCHEDULE PART 1/3					
						DRAWN HHUES	DESIGNED HHUES	CHECKED RBAM	DATE June,22	SCALE AS SHOWN	DRAWING No. EL-IDZ- RDF11/21-20